






④ **USB2.0 COMPLIANT**



NOTES:

- 1. Material:
 - 1.1 Housing: PBT+30%GF UL94V-0, Color Black
 - 1.2 Shell: SPCC
 - 1.3 Contact :Brass
- 2. FINISH:
 - 2.1 Contact Area: Selective 5u"Au
 - Solder Area: Tin Plated
 - Under: Ni Plated
- 3. MECHANICAL:
 - 3.1 Mating Force: 3.57kgf Max.
 - 3.2 Unmating Force: 1.02kgf Min
 - 3.3 Durability: 1500 cycles Min
- 4. ELECTRICAL:
 - 4.1 Current Rating: 1.5A
 - 4.2 Dielectric Strength: 500V AC FOR 1 MINUTE
 - 4.3 Contact Resistance: 30mΩ Max
 - 4.4 Insulation Resistance: 1000 MΩ Min
- ② 5. Operating temperature: -55°C TO +85°C
- ② 6. Soldering temperature: 245°C±5°C for 3~5 Sec
- 7. PACKIING: Tray

RoHS compliant

Scale	Free					Date	Name	Customer-No.	
TOLERANCE		④	Update	24.07.2019	Xavier	Drawn	07.06.2013	Winnie	
.X	±0.30	③	Change the Pin number	03.04.2014	Winnie	Approved	03.04.2014	Winnie	
.XX	±0.20	②	Add the soldering temperature	27.12.2013	Winnie			ASSMANN WSW-No. ① AU-Y1008	
.XXX	±0.10	①	Update the P/N	10.12.2013	Winnie			Drawing-No.	
DIM	TOL	①	Update the P/N	10.12.2013	Winnie			ASS 5781 CO	rev04
X.°	±5°	①	Drawn	07.06.2013	Winnie			Replace	SHEET
Angle	TOL	①	Drawn	07.06.2013	Winnie				
UNIT	mm	Id.	Modification	Date	Name				