

SERIES: VOF-S12B | **DESCRIPTION:** AC-DC POWER SUPPLY

FEATURES


- universal input range (90 ~ 264 Vac)
- Class B emissions (EN55032/CISPR/FCC)
- certified to IEC/EN/UL 62368-1
- designed to meet IEC/EN 60335
- short circuit protection
- over voltage protection
- < 75 mW no-load power consumption
- Class II



| MODEL | output voltage (Vdc) | output current | | output power max (W) | ripple and noise ¹ max (mVp-p) | efficiency ² typ (%) |
|-------------|-------------------------|----------------|------------|----------------------------|---|---------------------------------------|
| | | min (A) | max (A) | | | |
| VOF-S12B-5 | 5 | 0 | 2.0 | 10 | 100 | 80 |
| VOF-S12B-9 | 9 | 0 | 1.34 | 12 | 100 | 85 |
| VOF-S12B-12 | 12 | 0 | 1.0 | 12 | 120 | 85 |
| VOF-S12B-15 | 15 | 0 | 0.8 | 12 | 150 | 85 |
| VOF-S12B-24 | 24 | 0 | 0.5 | 12 | 240 | 87 |

Notes: 1. At full load, nominal input, 20 MHz bandwidth oscilloscope, with 1 µF ceramic and 10 µF electrolytic capacitors on the output.
 2. At 230 Vac, full load, 25°C.
 3. All specifications are measured at Ta=25°C, nominal input voltage, and 75% rated output load unless otherwise specified.

PART NUMBER KEY



INPUT

| parameter | conditions/description | min | typ | max | units |
|-----------------|------------------------------|-----|-----|------|-------|
| voltage | | 90 | | 264 | Vac |
| | | 120 | | 370 | Vdc |
| frequency | | 47 | | 63 | Hz |
| current | | | | 400 | mA |
| inrush current | at 240 Vac, cold start, 25°C | | | 50 | A |
| leakage current | at 264 Vac | | | 0.25 | mA |

OUTPUT

| parameter | conditions/description | min | typ | max | units |
|----------------------------|--|-----|-------|-------|-------|
| capacitive load | 5 Vdc output models | | | 2,000 | μF |
| | 9 Vdc output models | | | 1,340 | μF |
| | 12 Vdc output models | | | 1,000 | μF |
| | 15 Vdc output models | | | 800 | μF |
| | 24 Vdc output models | | | 500 | μF |
| initial set point accuracy | at 100% load | | | ±2 | % |
| line regulation | measured at high line to low line at full load | | | ±1 | % |
| load regulation | measured at 10%~100% load | | | ±1 | % |
| start-up time | | | | 3 | s |
| hold-up time | at 115 Vac | | 10 | | ms |
| switching frequency | | | 65 | | kHz |
| temperature coefficient | | | ±0.05 | | %/°C |

PROTECTIONS

| parameter | conditions/description | min | typ | max | units |
|--------------------------|------------------------|-----|-----|------|-------|
| over voltage protection | hiccup, auto recovery | | | | |
| | 5 Vdc output models | | | 6.3 | Vdc |
| | 9 Vdc output models | | | 12.6 | Vdc |
| | 12 Vdc output models | | | 15.8 | Vdc |
| | 15 Vdc output models | | | 18.9 | Vdc |
| | 24 Vdc output models | | | 31.5 | Vdc |
| short circuit protection | hiccup, auto recovery | | | | |

SAFETY & COMPLIANCE

| parameter | conditions/description | min | typ | max | units |
|--------------------------------|--|-------|-----|-----|-------|
| isolation voltage | input to output for 1 minute | 3,000 | | | Vac |
| isolation resistance | | 100 | | | MΩ |
| safety approvals | certified to IEC/EN/UL 62368-1 designed to meet IEC/EN 60335 | | | | |
| safety class | | | | | |
| conducted emissions | EN55032 2015, EN61000-6-3 2007+A1: 2011+AC: 2012, Class B, 47 CFR FCC Part 15 Subpart B (Class B) | | | | |
| radiated emissions | EN55032 2015, EN61000-6-3 2007+A1: 2011+AC: 2012, Class B, 47 CFR FCC Part 15 Subpart B (Class B) | | | | |
| harmonic current emissions | EN61000-3-2:2014 | | | | |
| voltage fluctuations & flicker | EN61000-3-3:2013 | | | | |
| ESD | IEC61000-4-2:2008 | | | | |
| radiated immunity | IEC61000-4-3:2010 | | | | |
| EFT/burst | IEC61000-4-4:2012 | | | | |
| surge | IEC61000-4-5:2014 | | | | |

SAFETY & COMPLIANCE (CONTINUED)

| parameter | conditions/description | min | typ | max | units |
|--------------------------------|--|-----|---------|-----|-------|
| conducted immunity | IEC61000-4-6:2013 | | | | |
| power frequency magnetic field | IEC61000-4-8:2009 | | | | |
| voltage dips & interruptions | IEC61000-4-11:2004 | | | | |
| MTBF | as per MIL-HDBK-217F, at 115 Vac, 25°C, GB | | | | |
| | 5 Vdc output model | | 580,000 | | hours |
| | 9 Vdc output model | | 870,000 | | hours |
| | 12 Vdc output model | | 660,000 | | hours |
| | 15 Vdc output model | | 740,000 | | hours |
| | 24 Vdc output model | | 620,000 | | hours |
| RoHS | yes | | | | |


Notes: 4. The power supply is considered a component which will be installed into final equipment. The final equipment still must be tested to meet the necessary EMC directives.

ENVIRONMENTAL

| parameter | conditions/description | min | typ | max | units |
|-----------------------|---|-----|-----|-------|-------|
| operating temperature | see derating curves | -40 | | 75 | °C |
| storage temperature | | -40 | | 85 | °C |
| operating humidity | non-condensing | | | 93 | % |
| altitude | | | | 5,000 | m |
| vibration | as per MIL-STD-810F Table 514.5C-VIII; 15~2000 Hz for 1 hour on each axis for 3 hours | | 4 | | G |
| shock | as per MIL-STD-810F Table 516.5, Table 516.5-1; for 10 ms on each axis 3 times | | 75 | | G |

DERATING CURVES

TEMPERATURE DERATING CURVE




MECHANICAL

| parameter | conditions/description | min | typ | max | units |
|------------|--|-----|-----|-----|--------|
| dimensions | 1.50 x 1.00 x 0.756 (38.10 x 25.40 x 19.20 mm) | | | | inches |
| weight | | | 16 | | g |

MECHANICAL DRAWING


units: inch [mm]
tolerance: ±0.020[±0.50]



| PIN CONNECTIONS | |
|-----------------|----------|
| PIN | Function |
| 1 | AC (N) |
| 2 | AC (L) |
| 3 | -Vo |
| 4 | +Vo |

INSTALLATION INSTRUCTIONS

The mounting holes should all be 1.5 mm in diameter. A minimum of 4 mm clearance is required for all four sides of the unit and a minimum of 5 mm clearance is required above the top surface of the unit.



REVISION HISTORY

| rev. | description | date |
|------|-------------------------------|------------|
| 1.0 | initial release | 02/13/2020 |
| 1.01 | updates to mechanical section | 04/08/2020 |
| 1.02 | derating curve updated | 04/27/2021 |

The revision history provided is for informational purposes only and is believed to be accurate.



Headquarters
20050 SW 112th Ave.
Tualatin, OR 97062
800.275.4899

Fax 503.612.2383
cui.com
techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.