


## Starter kit - AXC 1050 PN STARTERKIT - 2400361

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

AXC 1050 PN starter kit including AXC 1050 controller, AXL F BK PN bus coupler, AXL F DI/DO 16 I/O modules, power supply, PC Worx software with quick start guide, and additional accessories




### Your advantages

- Quick entry into automation with PROFINET thanks to step-by-step instructions for the test setup
- Structure with the latest automation station based on Axiocontrol and Axioline components
- Get started right away with a set of all required products



### Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 023250
GTIN	4055626023250

### Technical data

#### Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

### Articles in set

Controller - AXC 1050 - 2700988



Axio control for direct open-loop control of Axioline I/Os. With 2 Ethernet interfaces and programming capabilities according to IEC 61131-3. Complete with connector connector and labeling field.

## Starter kit - AXC 1050 PN STARTERKIT - 2400361

### Articles in set

Bus coupler - AXL F BK PN - 2701815



Axioline F, Bus coupler, PROFINET, RJ45 jack, transmission speed in the local bus: 100 Mbps, degree of protection: IP20, including bus base module and Axioline F connector

---

I/O module - AXL F DI16/4 2F - 2688022



Axioline F, Digital input module, Digital inputs: 16, 24 V DC, connection technology: 4-conductor, transmission speed in the local bus: 100 Mbps, degree of protection: IP20, including bus base module and Axioline F connectors

---

I/O module - AXL F DO16/3 2F - 2688048



Axioline F, Digital output module, Digital outputs: 16, 24 V DC, connection technology: 3-conductor, transmission speed in the local bus: 100 Mbps, degree of protection: IP20, including bus base module and Axioline F connectors

---

License - PC WORX EDUCATION LIC - 2700205



License

---

Power supply unit - STEP-PS/ 1AC/24DC/1.75 - 2868648



Primary-switched STEP POWER power supply for DIN rail mounting, input: 1-phase, output: 24 V DC/1.75 A

---

# Starter kit - AXC 1050 PN STARTERKIT - 2400361

## Articles in set

Patch cable - FL CAT5 PATCH 1,0 - 2832276



Patch cable, CAT5, assembled, 1 m

Connecting cable - CAB-USB A/MICRO USB B/2,0M - 2701626



Connecting cable, for connecting the controller to a PC for PC Worx and LOGIC+, USB A to micro USB B, 2 m in length.

## Classifications

### eCl@ss

eCl@ss 10.0.1	27242219
eCl@ss 11.0	27242219
eCl@ss 5.0	27242700
eCl@ss 5.1	27242700
eCl@ss 6.0	27242200
eCl@ss 7.0	27242207
eCl@ss 9.0	27242219

### ETIM

ETIM 2.0	EC000236
ETIM 3.0	EC000236
ETIM 4.0	EC002581
ETIM 6.0	EC002581
ETIM 7.0	EC002581

### UNSPSC

UNSPSC 13.2	39122114
UNSPSC 19.0	39122114

Phoenix Contact 2021 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>