


This document is the property of Amphenol Corporation and is delivered on the express condition that it is not to be disclosed, reproduced or used, in whole or in part, for manufacture or sale by anyone other than Amphenol Corporation without its prior consent, & that no right is granted to disclose or to use any information in this document.

# Customer Drawing



RECOMMENDED P.C.B LAYOUT  
TOLERANCE ± 0.05



## Dimensions

Positions	A	B	C
9	30.81	24.99	16.33
15	39.19	33.32	24.66
25	53.04	47.04	38.38
37	69.32	63.50	54.84

## REVISIONS


SYM	ECN	DESCRIPTION	DATE	APPROVED
1	HK--	First Release Drawing	03/10/08	IP
2	HK--	Update the Drawing	05/17/12	IP
3	HK--	Update the Drawing	10/17/12	IP
4	HK--	Update the Drawing	04/08/13	IP

## D-SUB TECHNICAL DATA

SHELL : SPCC, 50u" min nickel over 50u" copper  
 BODY : PBT UL 94V-0 Color:Black  
 CONTACTS : Copper Alloy  
 Gold flash over 50u" min nickel on mating area.  
 100u" min tin over 50u" min nickel on solder area.  
 BOARDLOCK: Copper Alloy. Tin plated  
 REAR NUT : Copper Alloy, nickel plated  
 ELECTRICAL : Voltage rating 250 VAC(Rms) Max  
 Current rating 3A.  
 Withstanding Voltage >1000 VAC Rms for one minute  
 Insulation resistance >1000 M Ohms  
 Contact resistance 25 mOhms Max.  
 MARKING : Amphenol...(Series No.)  
 Commercial reference  
 Manufacturing date

## PRODUCT CODE

L 77 SD X XX S 1A CH 4R



UNLESS OTHERWISE SPECIFIED TOLERANCES		APPROVAL		DATE
U.S.	METRIC	DRAWN	Checked	DATE
.X +/-	0.50	Felix Liu		04/18/13
.XX +/-	0.30			
.XXX +/-	0.20	Checked Tony Tang		04/18/13
FRACTIONS +/-				
ANGLES +/-	5°			
FOR MATERIALS AND FINISHES SEE NOTES		DRAWING FILE :		
REMOVE SHARP EDGES		ANGLE OF PROJECTION		
DIMENSIONS				
U.S.	INCHES			
METRIC	MM			

Amphenol

Amphenol East Asia Limited

TITLE  
Stamped and formed contact,SD series

SIZE	DRAWING NO.	REV.
A4	C L77SDXXXS1ACH4R	4
SCALE	NONE	SHEET 1 OF 1